

# EDGE 4

AESTHETIC SQUARE CYLINDER  
WITH POWER CORD FREE DESIGN

## Housing

Diameter : Ø4" | Height : 9.5" | Weight : 8 lbs

## Material

Housing : Extruded Aluminum

Reflector : Flow Forming Aluminum

## Power Input

15W, 25W, 35W, 45W | 120V-277V

## Lumen Output

1,330 lm (15W), 2,160 lm (25W), 3,150 lm (35W), 4,000 lm (45W)

## Dimming

Standard 0-10V : Dims to 10%

Superior 0-10V : Dims to 1%

DMX : High resolution dims to 0.1% (Supports ANSI E1.20 RDM protocol)

LDE1 : Hi-Lume 1% EcoSystem LED Driver with Soft-on, Fade-to-Black

TRC : Linear line-voltage phase control, dims to 1%

## Color Quality

CRI 85, CRI 93

## Rated Life

> 100,000 Hours (L70)

## Finish



Black



White

## Color Temperature



2700K



3000K



3500K



4000K

## Optics



35°



45°



60°



Wide

## Mounting



Stem  
Mount



Cord  
Mount



Power Line  
Mount



Surface  
Mount

## Warranty

5 Year limited warranty

## Listing



Precision Engineered For High Performance.

4-inch aperture square pendant with a lumen package range of 1,330 - 4,000 lumens.

Compatible with all 0-10v dimming controls and DMX dimming with ANSI E1.20 RDM Protocol.

This aesthetic luminaire is designed to elevate and illuminate beautiful spaces.



SPECIFICATION SHEET

**EDGE 4** AESTHETIC SQUARE CYLINDER WITH POWER CORD FREE DESIGN



**SPECIFICATION**

<b>PROJECT NAME</b>	<b>DATE</b>
<input type="text"/>	<input type="text"/>
<b>CATALOG #</b>	<b>QUANTITY</b>
<input type="text"/>	<input type="text"/>

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

<input type="text" value="ED4"/>	<b>MODEL</b>	<b>EDGE 4</b>		
<input type="text"/>	<b>WATTAGE</b>	<b>15</b> 15W <b>45</b> 45W	<b>25</b> 25W	<b>35</b> 35W
<input type="text"/>	<b>CCT / CRI</b>	<b>278</b> 2700K / CRI 85 <b>309</b> 3000K / CRI 93 <b>408</b> 4000K / CRI 85	<b>279</b> 2700K / CRI 93 <b>358</b> 3500K / CRI 85	<b>308</b> 3000K / CRI 85 <b>359</b> 3500K / CRI 93
<input type="text"/>	<b>VOLTAGE</b>	<b>UNV</b> 120-277V	<b>120</b> 120V	
<input type="text"/>	<b>DIMMING</b>	<b>STV</b> Standard 0-10V dims to 10% <b>TRC</b> <sup>2</sup> Linear line-voltage phase control, dims to 1%	<b>SPV</b> Superior 0-10V dims to 1% <b>LDEI</b> <sup>3</sup> Hi-Lume 1% EcoSystem LED Driver with Soft-on, Fade-to-Black	<b>DMXR</b> <sup>1</sup> DMX dims to 0.1% (RJ45 Sockets)
<input type="text"/>	<b>BEAM ANGLE</b>	<b>35</b> 35° <b>WD</b> <sup>4</sup> Wide	<b>45</b> 45°	<b>60</b> 60°
<input type="text"/>	<b>FINISH</b>	<b>BLK</b> Black	<b>WHT</b> White	
<input type="text"/>	<b>TRIM FINISH</b>	<b>BLK</b> Black	<b>SLV</b> Silver	
<input type="text"/>	<b>MOUNTING</b>	<b>PL#(2/4/6/8/10)</b> <sup>5</sup> Power Line Mount (2, 4, 6, 8, and 10 ft) <b>ST4</b> Stem 4ft	<b>CM10</b> Cord Mount 10ft	<b>ST2</b> Stem 2ft <b>SUM</b> <sup>6</sup> Surface Mount
<input type="text"/>	<b>ACCESSORIES</b>	<b>RM</b> <sup>7</sup> Remote Power	<b>FCS</b> <sup>8</sup> Field Cut Stem Adapter Kit	

CLEAR FORM

<sup>1</sup> DMXR must be specified with RM option  
<sup>2</sup> TRC must be specified with 120V  
<sup>3</sup> LDEI must be specified with RM option  
<sup>4</sup> WD option reduces delivered lumens by ~20%  
<sup>5</sup> Replace “#” with the required length designation. ex: PL2, PL4  
<sup>6</sup> SUM is not compatible with RM  
<sup>7</sup> RM comes with a shallow canopy  
<sup>8</sup> FCS is not compatible with PL, CM10, SUM

SPECIFICATION SHEET

**EDGE 4** AESTHETIC SQUARE CYLINDER WITH POWER CORD FREE DESIGN



**TECHNICAL DETAILS**

**Electrical**

- 1,330 lm (15W), 2,160 lm (25W), 3,150 lm (35W), 4,000 lm (45W)
- Power Input : Universal (120-277V)
- Operating Temperature : 14°F~104°F
- Surge Protection : Built-in is 2KV
- Power Factor Greater than 0.9

**LED Features**

- Color Temperature : 2700K, 3000K, 3500K, 4000K
- CRI 85, CRI 93
- UGR ≤19
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

**Optics**

- Flow Forming Aluminum Reflector
- Beam Angle : 35°, 45°, 60°, WD

**Advanced Dimming**

- Proprietary VX Driver™ is incorporated to all dimming options for video flicker-free lighting
- Standard 0-10V : Dims to 10%
- Superior 0-10V : Dims to 1%
- DMX : High resolution dims to 0.1% (Supports ANSI E1.20 RDM protocol)
- LDE1 : Hi-Lume 1% EcoSystem LED Driver with Soft-on, Fade-to-Black
- TRC : Linear line-voltage phase control, dims to 1%

**Housing**

- Diameter : Ø4"
- Height : 9.5"
- Weight : 8 lbs
- Material : Extruded Aluminum

**Mounting**

- PowerLine Mount 2ft, 4ft, 6ft, 8ft, 10ft with High Lumen Power Suspension
- Stem 2ft or 4ft
- Cord Mount 10ft
- Surface Mount

**Warranty**

- 5-year limited warranty

**Listing**

- ETL Damp Location Listed
- CE
- FCC

**PERFORMANCE SUMMARY\***

Delivered Lumens				
CCT/WATTAGE	2700K	3000K	3500K	4000K
<b>15W</b>	1,200lm	1,260lm	1,300lm	1,330lm
<b>25W</b>	1,950lm	2,030lm	2,100lm	2,160lm
<b>35W</b>	2,850lm	2,910lm	3,060lm	3,150lm
<b>45W</b>	3,550lm	3,700lm	3,820lm	4,000lm

Current Consumption		
WATTAGE / VOLT	120V	277V
<b>15W</b>	0.14A	0.06A
<b>25W</b>	0.23A	0.1A
<b>35W</b>	0.32A	0.14A
<b>45W</b>	0.41A	0.18A

\* Beam Angle 35° Tolerance ±8%

\* For specifications requiring a CRI of 93, apply a 0.75 multiplier to the lumen output values listed.


SPECIFICATION SHEET

**EDGE 4** AESTHETIC SQUARE CYLINDER WITH POWER CORD FREE DESIGN



**PHOTOMETRICS**

Below is a typical photometric representation of the Edge 4 fixture. Please download IES files to ensure exact photometric value.




**DMX REQUIREMENTS**

The Edge 4 fixture with DMX is a **single channel dmx** unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

The fixture can be connected with RJ45 sockets. DMX cables **are not** included; please refer to compatible DMX cabling list for more information. The final fixture on each daisy chain should be terminated by the use of a DMX terminator purchased from a 3rd party or from Meteor.

CONNECTION	RJ45 (CAT5e)
Common	WHITE/BROWN(PIN7) & BROWN (PIN 8)
Signal -	ORANGE (PIN 2)
Signal +	WHITE/ORANGE (PIN 1)
Spare	-
Spare	-



**COMPATIBLE DMX CABLING LIST**

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable **must not be used to carry DMX**. Network cable (Cat5, 5e or 6 cable) may be used to carry DMX in an installation; however special consideration must be given to shielding and termination. Under no circumstances should solid core cable like Cat5 be terminated into a screw down connector.

Meteor recommends the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed.

**COMPATIBLE LDE1 DIMMER LIST**

LUTRON PART NO.						
RMJ-ECO32-DV-B	FCJ/FCJS-ECO	QSN-1ECO-S	QSN-2ECO-S	QSGRJ-_E	QSGR-_E	QP2-__2C
QP2-__4C	QP2-__6C	QP2-__8C	LQSE-2ECO-D			

SPECIFICATION SHEET


**EDGE 4** AESTHETIC SQUARE CYLINDER WITH POWER CORD FREE DESIGN




**COMPATIBLE TRC DIMMER LIST**

PART NO.					
Lutron S-603PG	Lutron DVCL-153P	Lutron DVLV-600P	Lutron TGCL-153P	Lutron S-600P	Lutron DVELV-303P
Lutron SELV-300P	Lutron TG-600P	Lutron DVLV-600P	Lutron LG-600P	Lutron CT-103P	Lutron MAELV-600
Lutron FAELV-500	Leviton IPI06-1LZ	Leviton 6631-2	Leviton VPE06	Leviton 6683-IW	Leviton 6161
Leviton 6633-P	Leviton IPE04	Cooper DLC03P	Cooper SLC03P	Cooper DAL06P	Lightolier ZP260QEW

**DIMENSIONS**



**DIMENSIONS**




SPECIFICATION SHEET

**EDGE 4** AESTHETIC SQUARE CYLINDER  
WITH POWER CORD FREE DESIGN



**MOUNTING OPTIONS**

*\*Standard Driver-In Canopy Mounting Options*



**REMOTE DRIVER CANOPY MOUNTING OPTIONS**

