HueCraft Submersible 6

HueCraft HS6/Archi-Color® RGBL

SPECIFICATION SHEET

The HueCraft Submersible series is a durable family of underwater luminaires designed for fountains and architectural water features. Constructed with marine-grade stainless steel and sealed with waterproof silicone gaskets, HueCraft Submersible delivers reliable performance in fully submerged environments. Two compact sizes support a broad range of applications while maintaining a clean look.

A selection of narrow spot and wider flood beam options allows light to be tailored for focused accents or broad underwater washes. Static white and dynamic color options accommodate a range of lighting effects, while adjustable surface-mount and in-grade mounting options provide installation flexibility.





FINISH



316L
Stainless Steel

CCT




RGB + Lime

OPTICS



10° 15° 25° 40° 60° 20°x40°

MOUNTING



Adjustable Surface

Ingrade

Archi-Color® RGBL

Now tailored for outdoor applications, our refined RGBL system introduces Lime LEDs for better performance and higher efficacy. The expanded spectrum enhances the colors that matter most outdoors—richer ambers, natural reds, deeper greens, and the golden-yellow glow reminiscent of sodium lighting. Archi-Color also enables balanced white light mixing, delivering cleaner, more natural tones alongside vivid, saturated color.

Stainless-steel Underwater Luminaires

HueCraft Submersible series features an IP68-rated construction with a 316L stainless steel housing, corrosion-resistant fasteners, and an anti-aging waterproof silicone gasket. A clear safety glass lens and precision sealing protect internal components from water ingress, ensuring reliable operation in demanding underwater environments up to 15 ft deep.

LISTING

CE FC IP68 IK08

HueCraft Submersible 6

ELECTRICAL

Power Input	25W | 120-277 VAC
Power Factor	> 0.9
Driver Location	Remote Location

PHYSICAL

Housing Material	316L Stainless Steel Housing, Anti-aging waterproof silicone gasket, Clear safety glass, Nickel plated brass cable gland
Finish	Stainless Steel
Dimensions	Adjustable Surface Mount: 5.91" × 3.46" × 6.28", ø5.91" Ingrade: ø6.69" x 5.90"
Weight	6.2 lbs / 2.8 kg
Adjustability	Tiltable 60°, Rotation 0 - 350°
Mounting	Adjustable Surface Mount, Ingrade

PHOTOMETRIC PERFORMANCE

Lumen Output	806.4 lm (40°)
Beam Angle	10°, 15°, 25°, 40°, 60°, 20°x40°
Colors	Archi-Color® RGB + Lime
Lumen Maintenance	Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 65,000 Hrs

CONTROL

Control	4 Channel DMX
Dimming	DMX high resolution 16 bit dimming curve dims to 0.1%, supports ANSI E1.20 RDM protocol
Maximum Fixtures	Each remote power box can support up to 3 fixtures, with a maximum of 32 fixtures per daisy chain

ENVIRONMENTAL

Operating Temperature	32°F ~ 122°F / 0°C ~ 50°C
Maximum Depth	15 ft
Ingress Protection	IP68
Impact Resistance	IK08
Listing	UL 379 (Remote Power Box) , UL 676 (Fixture Body), CE, FCC

WARRANTY

Warranty	5-year limited warranty

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

HueCraft Submersible 6

SPECIFICATION SHEET
HueCraft HS6/Archi-Color® RGBL

CATALOG

PROJECT	TYPE	QUANTITY

PRODUCT CONFIGURATOR

Try our **product configurator** on our website to easily specify your requirements and add items to a fixture list.

HS6	25	RGBL	UNV	DMX	
MODEL	**WATTAGE**	**CCT / CRI**	**VOLTAGE**	**DIMMING**	**OPTIC**
HS6 HueCraft Submersible 6”	**25** 25W, Ø6”	**RGBL** RGB + Lime	**UNV** 120 - 277 VAC	**DMX** DMX high resolution 16 bit dimming curve dims to 0.1%, supports ANSI E1.20 RDM protocol	**10** 10° **15** 15° **25** 25° **40** 40° **60** 60° **2040** 20° x 40°

ST		
FINISH	**MOUNTING**	**CABLE**
ST Stainless Steel	**SUM** Adjustable Surface Mount **ING** Ingrade	**50** 50ft **100** 100ft **150** 150ft

CATALOG - REMOTE POWER BOX

REMOTE POWER BOX

HSR4		
MODEL	**OUTPUT PORT**	**OPTION**
HSR4 HueCraft Submersible Remote Power Box (4ch)	**1P** 1 Port **2P** 2 Ports **3P** 3 Ports	**NON** No Terminator **DMXT** DMX Terminator Included

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

PERFORMANCE

	COLOR	LUMEN
10°	Red	112.6 lm
	Green	179.9 lm
	Blue	95.3 lm
	Lime	273.4 lm
	Full On	664.3 lm
15°	Red	110.5 lm
	Green	151 lm
	Blue	78.1 lm
	Lime	238.8 lm
	Full On	651.8 lm
25°	Red	110.1 lm
	Green	150.4 lm
	Blue	77.9 lm
	Lime	237.9 lm
	Full On	649.5 lm
40°	Red	136.7 lm
	Green	186.8 lm
	Blue	96.7 lm
	Lime	295.3 lm
	Full On	806.4 lm
60°	Red	131.6 lm
	Green	163 lm
	Blue	84.3 lm
	Lime	257.6 lm
	Full On	703.4 lm
20x40°	Red	73 lm
	Green	99.8 lm
	Blue	51.7 lm
	Lime	157.7 lm
	Full On	430.6 lm

Note: Tolerance ±10%

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.


HueCraft Submersible 6

SPECIFICATION SHEET
HueCraft HS6/Archi-Color® RGBL

PHOTOMETRICS*


***** Data measured @ RGBL full on

10°




	Center Beam(fc)	Beam Diameter(ft)
8.3ft	90.1	1.7
16.7ft	22.5	3.4
25ft	10	5.1
33.3ft	5.63	6.8
41.7ft	3.60	8.5
50ft	2.50	10.2

15°




	Center Beam(fc)	Beam Diameter(ft)
8.3ft	51.2	2.4
16.7ft	12.8	4.7
25ft	5.69	7.1
33.3ft	3.20	9.4
41.7ft	2.05	11.8
50ft	1.42	14.1

25°




	Center Beam(fc)	Beam Diameter(ft)
8.3ft	31.2	3.2
16.7ft	7.79	6.4
25ft	3.46	9.6
33.3ft	1.95	12.8
41.7ft	1.25	16
50ft	0.87	19.2

40°




	Center Beam(fc)	Beam Diameter(ft)
5ft	49.4	3.9
10ft	12.3	7.8
15ft	5.49	11.7
20ft	3.09	15.7
25ft	1.98	19.6
30ft	1.37	23.5

60°



	Center Beam(fc)	Beam Diameter(ft)
5ft	23.5	5.3
10ft	5.87	10.6
15ft	2.61	15.9
20ft	1.47	21.2
25ft	0.94	26.5
30ft	0.65	31.8

20x40°



	Center Beam(fc)	Beam Diameter(ft)
5ft	28.4	2.8/4.6
10ft	7.10	5.7/9.5
15ft	3.16	8.5/14
20ft	1.77	11.4/18.7
25ft	1.14	14.2/23.4
30ft	0.79	17.1/28.3

DMX CHART

The HueCraft Submersible 6 fixture is a four channel DMX unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

DMX ADDRESS


Fixture # \ Channel	Red Control (ex. X)	Green Control (ex. X+1)	Blue Control (ex. X+2)	Lime (ex. X+3)
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

COMPATIBLE DMX CABLING

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable must not be used to carry DMX. We recommend the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed. A DMX terminator is also required at the end of each DMX chain to ensure proper signal transmission and prevent data reflection.

CONNECTION

* This diagram is for illustrative purposes only. All installations must comply with applicable electrical codes and safety standards. Follow NEC requirements and consult a qualified professional for proper implementation.




Note:
- Maximum fixtures per remote power box: 3 fixtures
- Maximum fixtures per daisy chain: 32 fixtures


Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DIMENSIONS

ADJUSTABLE SURFACE MOUNT



INGRADE




exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DIMENSIONS

REMOTE POWER BOX



Note:
- The remote power box is IP65 rated and suitable for wet locations
- Max remote distance 150ft

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.