

SPECIFICATION SHEET

The HueCraft Submersible series is a durable family of underwater luminaires designed for fountains and architectural water features. Constructed with marine-grade stainless steel and sealed with waterproof silicone gaskets, HueCraft Submersible delivers reliable performance in fully submerged environments. Two compact sizes support a broad range of applications while maintaining a clean look.

A selection of narrow spot and wider flood beam options allows light to be tailored for focused accents or broad underwater washes. Static white and dynamic color options accommodate a range of lighting effects, while adjustable surface-mount and in-grade mounting options provide installation flexibility.

FINISH



316L
Stainless Steel

CCT



RGB + Lime

OPTICS



10°



15°



25°



40°



60°



20°x40°

MOUNTING



Adjustable
Surface



Ingrade



Archi-Color® RGBL

Now tailored for outdoor applications, our refined RGBL system introduces Lime LEDs for better performance and higher efficacy. The expanded spectrum enhances the colors that matter most outdoors—richer ambers, natural reds, deeper greens, and the golden-yellow glow reminiscent of sodium lighting. Archi-Color also enables balanced white light mixing, delivering cleaner, more natural tones alongside vivid, saturated color.

Stainless-steel Underwater Luminaires

HueCraft Submersible series features an IP68-rated construction with a 316L stainless steel housing, corrosion-resistant fasteners, and an anti-aging waterproof silicone gasket. A clear safety glass lens and precision sealing protect internal components from water ingress, ensuring reliable operation in demanding underwater environments up to 15 ft deep.

LISTING



HueCraft Submersible 8

SPECIFICATION SHEET
HueCraft HS8/Archi-Color® RGBL

ELECTRICAL

Power Input	45W 120-277 VAc
Power Factor	> 0.9
Driver Location	Remote Location

PHYSICAL

Housing Material	316L Stainless Steel Housing, Anti-aging waterproof silicone gasket, Clear safety glass, Nickel plated brass cable gland
Finish	Stainless Steel
Dimensions	Adjustable Surface Mount: 7.48" x 3.46" x 8.02", ø7.48" Ingrade: ø8.62" x 5.90"
Weight	4.6 lbs / 3.8kg
Adjustability	Tiltable 60°, Rotation 0 - 350°
Mounting	Adjustable Surface Mount, Ingrade

PHOTOMETRIC PERFORMANCE

Lumen Output	1,626.9 lm (40°)
Beam Angle	10°, 15°, 25°, 40°, 60°, 20°x40°
Colors	Archi-Color® RGB + Lime
Lumen Maintenance	Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 65,000 Hrs

CONTROL

Control	4 Channel DMX
Dimming	DMX high resolution 16 bit dimming curve dims to 0.1%, supports ANSI E1.20 RDM protocol
Maximum Fixtures	Each remote power box can support one fixture, with a maximum of 32 fixtures per daisy chain.

ENVIRONMENTAL

Operating Temperature	32°F ~ 122°F / 0°C ~ 50°C
Maximum Depth	15 ft
Ingress Protection	IP68
Impact Resistance	IK08
Listing	UL 379 (Remote Power Box) , UL 676 (Fixture Body), CE, FCC

WARRANTY

Warranty	5-year limited warranty
----------	-------------------------

CATALOG

PROJECT	TYPE	QUANTITY
---------	------	----------

PRODUCT CONFIGURATOR [↗](#)

Try our **product configurator** on our website to easily specify your requirements and add items to a fixture list.

HS8	45	RGBL	UNV	DMX	
MODEL	WATTAGE	CCT / CRI	VOLTAGE	DIMMING	OPTIC
HS8 HueCraft Submersible 8"	45 45W	RGBL RGB + Lime	UNV 120 - 277 VAC	DMX DMX high resolution 16 bit dimming curve dims to 0.1%, supports ANSI E1.20 RDM protocol	10 10° 15 15° 25 25° 40 40° 60 60° 2040 20° x 40°

ST		
FINISH	MOUNTING	CABLE
ST Stainless Steel	SUM Adjustable Surface Mount ING Ingrade	50 50ft 100 100ft 150 150ft

CATALOG - REMOTE POWER BOX

REMOTE POWER BOX

HSR4	1P	
MODEL	OUTPUT PORT	OPTION
HSR4 HueCraft Submersible Remote Power Box (4ch)	1P 1 Port	NON No Terminator DMXT DMX Terminator Included


PERFORMANCE

	COLOR	LUMEN
10°	Red	255.6 lm
	Green	360.3 lm
	Blue	191 lm
	Lime	547.7 lm
	Full On	1,330.7 lm
15°	Red	223.3 lm
	Green	305.2 lm
	Blue	158 lm
	Lime	482.5 lm
	Full On	1,317.3 lm
25°	Red	220.2 lm
	Green	300.9 lm
	Blue	155.7 lm
	Lime	475.7 lm
	Full On	1,298.8 lm
40°	Red	275.9 lm
	Green	376.9 lm
	Blue	195 lm
	Lime	595.9 lm
	Full On	1,626.9 lm
60°	Red	217.3 lm
	Green	297 lm
	Blue	153.7 lm
	Lime	469.5 lm
	Full On	1,281.9 lm
20x40°	Red	123.7 lm
	Green	169 lm
	Blue	87.4 lm
	Lime	267.3 lm
	Full On	729.8 lm

Note: Tolerance $\pm 10\%$

PHOTOMETRICS*

* Data measured @ RGBL full on



DMX CHART

The HueCraft Submersible 8 fixture is a four channel DMX unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

DMX ADDRESS


Fixture # \ Channel	Red Control (ex. X)	Green Control (ex. X+1)	Blue Control (ex. X+2)	Lime (ex. X+3)
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

COMPATIBLE DMX CABLING

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable must not be used to carry DMX. We recommend the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed. A DMX terminator is also required at the end of each DMX chain to ensure proper signal transmission and prevent data reflection.

CONNECTION


* This diagram is for illustrative purposes only. All installations must comply with applicable electrical codes and safety standards. Follow NEC requirements and consult a qualified professional for proper implementation.




- Note:**
- Maximum fixtures per remote power box: 1 fixtures
 - Maximum fixtures per daisy chain: 32 fixtures

DIMENSIONS

ADJUSTABLE SURFACE MOUNT




INGRADE



DIMENSIONS

REMOTE POWER BOX



Note:

- The remote power box is IP65 rated and suitable for wet locations
- Max remote distance 150ft