exteria

HueCraft Linear

HueCraft HL/Archi-Color® RGBL

SPECIFICATION SHEET

HueCraft Linear merges powerful RGBL technology into a low-profile linear form. Offered in 1, 2, and 4-foot increments, it delivers smooth in-lens quad-chip color blending and consistent transitions across long runs. Built to withstand the elements with an IP67 rating, HueCraft Linear features waterproof quick-connectors for easy installation.



COLOR



Archi-Color® RGBL

FINISH



Matte Black



Matte White



Custom RAL

CCT



RGB + 3000K



RGB + 4000K



RGB + 6500K



RGB + Lime



RGB + Amber



Tunable White

OPTICS



15°



30°



45°



60°



15°x60°



60°x15°

MOUNTING



Swivel Bracket



Cantilever Arm

Archi-Color® RGBL

Now tailored for outdoor applications, our refined RGBL system introduces Lime LEDs for better performance and higher efficacy. The expanded spectrum enhances the colors that matter most outdoors—richer ambers, natural reds, deeper greens, and the golden-yellow glow reminiscent of sodium lighting. Archi-Color also enables balanced white light mixing, delivering cleaner, more natural tones alongside vivid, saturated color.

DriveMax™

Take your lighting further, drive single color channels up to 80% of fixture power, or dual channels simultaneously at 100%. Achieve bolder effects with greater efficiency.

LISTING









ELECTRICAL

Power Input	30W, 60W, 120W, 120-277 VAC
Power Factor	> 0.9
Driver Location	Integral
Surge Protection	Integral 4kV surge protector
Flicker-Free	Proprietary VX Driver™ is incorporated to all dimming options for video flicker-free lighting
High-Output Channel Drive	DriveMax™ allows individual color channels to operate at up to 80% of the fixture's total power, or two channels simultaneously at full output. *Channel drive capability may vary depending on configuration. Refer to the Performance section for full details.*

PHYSICAL

Housing Material	High pressure die-cast aluminum, tempered glass
Finish	Black, White, Custom RAL, Optional C5-M anticorrosion coating
Dimensions	Length x 3.17" x 3.17"
Housing Length	1 ft, 2 ft, 4 ft
Maximum Fixtures	Maximum 32 fixtures per DMX daisy chain; power limits allow 120V: 28 (1 ft/2 ft) or 15 (4 ft) and 240V+: 28 (1 ft/2 ft) or 24 (4 ft) fixtures per run.
Weight	2.64 lbs, 4.63 lbs, 8.81 lbs / 1.2 kg, 2.1 kg, 4 kg
EPA	Bracket: 0.219 ft^2 (Top) | 0.158 ft^2 (Front) | 0.036 ft^2 (Side)
Adjustability	90° Swivel
Mounting	Swivel Bracket, Cantilever Arm
Setback Distance	A 6-inch setback distance is recommended for optimal wall uniformity

PHOTOMETRIC PERFORMANCE

Lumen Output	6,900 lm (@4ft, 15° RGBL)
Beam Angle	15°, 30°, 45°, 60°, 15°x60°, 60°x15°
Colors	Archi-Color® RGB + Lime
Color Rendering	CRI 85+
Lumen Maintenance	Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 65,000 Hrs
LED Layout	Discreet quad-chip (4-in-1) RGBL

CONTROL

Control	4 Channel DMX
Dimming	DMX high resolution 16 bit dimming curve dims to 0.1%, supports ANSI E1.20 RDM protocol
Cable/Connections	Fixtures feature IP68-rated waterproof quick connectors for easy installation. Leader and jumper cables are sold separately to accommodate flexible system layouts.
Resolution	Default factory setting available in Per 1 ft Resolution (1 ft - 4 Channel DMX) or Per Fixture Resolution (1 Fixture - 4 Channel DMX)

ENVIRONMENTAL

Operating Temperature	-40°F ~ 122°F / -40°C ~ 50°C
Environment	ETL Wet Location
Ingress Protection	IP67
Listing	ETL, CE, FCC

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

WARRANTY

Warranty	5-year limited warranty

CATALOG - FIXTURE

PROJECT	TYPE	QUANTITY

PRODUCT CONFIGURATOR

Try our **product configurator** on our website to easily specify your requirements and add items to a fixture list.

	30		UNV	
MODEL	**WATTAGE**	**COLORS**	**VOLTAGE**	**DIMMING**
HL1 HueCraft Linear 1ft **HL2** HueCraft Linear 2ft **HL4** HueCraft Linear 4ft	**30** 30W per ft	**RGBL** RGB + Lime **RGBA**[1] RGB + Amber **RGB30**[1] RGB + 3000K **RGB40**[1] RGB + 4000K **RGB65**[1] RGB + 6500K **TNW**[1] Tunable White 1800K - 6500K	**UNV** 120 - 277 VAC	**DMX1F** DMX high resolution dims to 0.01%, 1 ft segment control **DMX2F**[2] DMX high resolution dims to 0.01%, 2 ft segment control **DMX4F**[3] DMX high resolution dims to 0.01%, whole fixture control

OPTIC	**FINISH**	**MOUNTING**	**CABLE ENTRY**	**ACCESSORIES**
15 15° **30** 30° **45** 45° **60** 60° **1560** 15° x 60° **6015** 60° x 15°	**BLK** Black **WHT** White **RAL**[4] Custom RAL	**BRK** Bracket **CA6** Cantilever Arm 6" **CA12** Cantilever Arm 12"	**RHT**[5] Right Side Input **LFT**[5] Left Side Input	**C5M**[6] C5-M Anticorrosion Coating **GSV**[7] Glare Shield Visor **SPD**[8] Surge Protector

Notes

1. Tailored control modes are available to simulate specific color temperatures or tonal ranges using the native **Archi-Color® RGBL** quad-chip engine.
2. DMX2F is not compatible with HL1
3. DMX4F is not compatible with HL1 and HL2
4. Custom RAL finish – please provide RAL number to your representative. Longer lead time required.
5. Please specify left or right side for power input when facing the wall to ensure correct mounting orientation.
6. Certified to ISO 12944 for high-corrosion environments. Ideal for coastal, marine, and industrial installations exposed to salt, moisture, or pollutants.
7. Use of the Glare Shield Visor (GSV) results in an estimated 20% reduction in lumen output.
8. Surge protector for up to 10KV. Applicable for unstable mains or facilities using high power machineries.

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

CATALOG - CABLE & CONNECTION

LEADER CABLE

HLC	LC	1	BLK	
MODEL	TYPE	LENGTH	FINISH	QUANTITY
HLC HueCraft Linear Connectors	**LC** Leader Cable (Male)	**1** 1 ft	**BLK** Black	

JUMPER CABLE

HLC	JC		BLK	
MODEL	TYPE	LENGTH	FINISH	QUANTITY
HLC HueCraft Linear Connectors	**JC** Jumper Cable (Male-Female)	**5** 5 ft **10** 10 ft **25** 25 ft	**BLK** Black	

DMX TERMINATOR

HLC	DMXT	
MODEL	TYPE	QUANTITY
HLC HueCraft Linear Connectors	**DMXT** DMX Terminator, one required for each run	

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

PERFORMANCE

	COLOR	WATTAGE	LUMEN	PEAK CANDELA
15°	**RGBL Full**	30 W	1,725 lm	8,083 cd
	Red	20.6 W	1,079 lm	5,054 cd
	Green	23.6 W	1,661 lm	7,782 cd
	Blue	24.4 W	372 lm	1,754 cd
	Lime	23.7 W	1,815 lm	8,500 cd
30°	**RGBL Full**	30 W	1,528 lm	2,945 cd
	Red	20.6 W	955 lm	1,841 cd
	Green	23.6 W	1,471 lm	2,836 cd
	Blue	24.4 W	330 lm	636 cd
	Lime	23.7 W	1,607 lm	3,097 cd
45°	**RGBL Full**	30 W	1,339 lm	1,169 cd
	Red	20.6 W	837 lm	731 cd
	Green	23.6 W	1,289 lm	1,125 cd
	Blue	24.4 W	289 lm	252 cd
	Lime	23.7 W	1,408 lm	1,229 cd
60°	**RGBL Full**	30 W	1,290 lm	1,085 cd
	Red	20.6 W	806 lm	679 cd
	Green	23.6 W	1,242 lm	1,045 cd
	Blue	24.4 W	278 lm	234 cd
	Lime	23.7 W	1,356 lm	1,142 cd
15x60°	**RGBL Full**	30 W	1,760 lm	2,866 cd
	Red	20.6 W	1,100 lm	1,792 cd
	Green	23.6 W	1,694 lm	2,759 cd
	Blue	24.4 W	380 lm	619 cd
	Lime	23.7 W	1,851 lm	3,014 cd

Note: Tolerance ±10%, CCT values are mixed from RGBL and not listed individually.
Approximate lumen outputs can be calculated by applying the following scale factors to the RGBL Full lumen value:

- 3000K = RGBL × 1.19
- 4000K = RGBL × 1.18
- 6500K = RGBL × 1.14


exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

PHOTOMETRICS*


***** Data messured @RGBL full on.

15°




Center Beam(fc)	Beam Diameter(ft)
8.3ft 117	6
16.7ft 29	12
25ft 12.9	18
33.3ft 7.3	24
41.7ft 4.6	30
50ft 3.2	36

30°




Center Beam(fc)	Beam Diameter(ft)
8.3ft 42.4	2.7
16.7ft 10.5	5.5
25ft 4.7	8.2
33.3ft 2.6	10.9
41.7ft 1.7	13.7
50ft 1.1	16.4

45°




Center Beam(fc)	Beam Diameter(ft)
5ft 46.6	4.8
10ft 11	9.6
15ft 5.7	14.5
20ft 2.9	19.3
25ft 1.8	24.1
30ft 1.3	28.9

60°



Center Beam(fc)	Beam Diameter(ft)
5ft 43.2	5.1
10ft 10.8	10.2
15ft 4.8	15.2
20ft 2.7	20.3
25ft 1.7	25.4
30ft 1.2	30.5


15x60°




Center Beam(fc)	Beam Diameter(ft)
5ft 113	2/4.4
10ft 28.2	4/8.9
15ft 12.5	6/13.3
20ft 7	8.1/17.7
25ft 4.5	10.1/22.2
30ft 3	12.1/26.6

ELLIPTICAL BEAM ANGLES

The first number refers to the beam width in the horizontal (H) axis, and the second number refers to the vertical (V) axis, **H° × V°**.



15° x 60°



60° x 15°

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DMX CHART

The HueCraft Linear is a four channel DMX unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

DMX ADDRESS (PERSONALITY 1-5)

Fixture # \ Channel	Red Control (ex. X)	Green Control (ex. X+1)	Blue Control (ex. X+2)	White / Lime / Amber (ex. X+3)
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

DMX ADDRESS (PERSONALITY 6-7)

Fixture # \ Channel	Intensity (ex. X)	Tunable White / Preset Color (ex. X+1)
#1	1	2
#2	3	4
#3	5	6

COMPATIBLE DMX CABLING


DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable must not be used to carry DMX. We recommend the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed. A DMX terminator is also required at the end of each DMX chain to ensure proper signal transmission and prevent data reflection.

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

CONNECTION

* This diagram is for illustrative purposes only. All installations must comply with applicable electrical codes and safety standards. Follow NEC requirements and consult a qualified professional for proper implementation.



MAXIMUM CONTINUOUS RUN

Input Voltage	Max Run Length per Power Drop	HL1	HL2	HL4
120V	40 ft	32 fixtures	20 fixtures	10 fixtures
277V	90 ft	32 fixtures	32 fixtures	22 fixtures



Note:
- Maximum fixtures per daisy chain: 32 fixtures
- Power drops: Power must be reintroduced at defined distances via a junction box due to voltage drop limitations.

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.


EPA VALUES

BRACKET


Top	Front	Side
		
0.219 ft^2	0.158 ft^2	0.036 ft^2

DIMENSIONS

BRACKET MOUNT




CANTILEVER ARM




Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DIMENSIONS


GLARE SHIELD VISOR



JUMPER CABLE



LEADER CABLE




exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DIMENSIONS

SETBACK DISTANCE



A 6-inch setback distance is recommended for optimal wall uniformity.


exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992


Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.

DIMENSIONS


CABLE ENTRY

LEFT SIDE INPUT







Bracket




Cantilever Arm 6" / 12"

RIGHT SIDE INPUT





Bracket



Cantilever Arm 6" / 12"

exterialighting.com
1860 S Carlos Ave, Ontario, California 91761
info@exterialighting.com | 213-992-9992

Exteria Lighting reserves the right to modify this product at any time without prior notice, as part of ongoing improvements. Please visit our website for the most current specifications.