SH-170

exteria

SPECIFICATION SHEET

Architectural, functional and green renewable. Exteria Solar LED Pavers blend efficient solar panels with a reliable ultracapacitor power solution, delivering eco-friendly and lasting illumination. Designed for minimal maintenance, these lights come in various square shapes, suitable for pathways and outdoor spaces. The anti-skid, wire-free, plug-and-play installation ensures a straightforward and practical lighting solution for your surroundings.

FINISH







Polished Stainless Steel



SUS316



CCT







Blue









Warm White

MOUNTING





Plug-and-Play

Designed for effortless deployment, the solar fixtures operate independently with no external wiring or transformers required. Installation is quick and clean, with no trenching, re-paving, or complex electrical connections, making them ideal for both new and retrofit projects.

LISTING









exterialighting.com Page 1



ELECTRICAL

WARRANTY Warranty

Power Storage	Ultracapacitor			
Charging Time	Requires approximately 6 hours of direct sunlight for a full charge			
PHOTOMETRIC PERFORMANCE				
Color Temperature	Amber, Blue, Green, Red, White, Warm White			
OPERATIONAL				
Operating Duration	Provides a minimum of 12 hours of illumination when fully charged, or 4–8 hours when charged under overcast weather conditions			
Control System	Integrated light-sensitive automatic on/off switch			
PHYSICAL				
Dimension	6.05" x 6.05"			
Material	SUS304 stainless steel, cast aluminum, GE super light permeable PC			
Rim Finish	Brushed/polished stainless steel; optional: SUS316 stainless steel/brass			
Weight	2.42lbs			
Compressive Strength	9,902 lbs (4,456 kg) — Pedestrian-only, not rated for vehicular loads			
ENVIRONMENTAL				
Operating Temperature	-4°F ~ 140°F			
Storage Temperature	-13°F~176°F			
Ingress Protection	IP68			
Listing	RoHS, CE, FCC			



3-year limited warranty

SH-170
Sh-170/Solar LED Paver

CATALOG

PROJECT TYPE QUANTITY

PRODUCT CONFIGURATOR 7

Try our **product configurator** on our website to easily specify your requirements and add items to a fixture list.

			HS
MODEL	сст	RIM FINISH	HOUSING
SH170C SH-170 Solar LED Paver	AMB Amber	BS Brushed Stainless Steel	HS Housing with Anchor Plate Included
SH170B Battery Sample	BLU Blue	PS Polished Stainless Steel	
	GEN Green	SS SUS316 Stainless Steel	
	RED Red	BR Brass	
	WHT White / 5500K - 6000K		
	WAM Warm White / 2800K - 3000K		

PERFORMANCE

COLOR	LUX(Average)
Amber	25 lx
Blue	25 lx
Green	50 lx
Red	65 lx
White	35 lx
Warm White	30 lx

SH-170
Sh-170/Solar LED Paver

DIMENSIONS 6.05"

