

SPECIFICATION SHEET

The HueCraft Submersible series is a durable family of underwater luminaires designed for fountains and architectural water features. Constructed with marine-grade stainless steel and sealed with waterproof silicone gaskets, HueCraft Submersible delivers reliable performance in fully submerged environments. Two compact sizes support a broad range of applications while maintaining a clean look.

A selection of narrow spot and wider flood beam options allows light to be tailored for focused accents or broad underwater washes. An RGBW version adds dynamic color capability, while the adjustable mounting supports on-site aiming.

FINISH




316L
Stainless Steel

CCT



RGBW

OPTICS



MOUNTING



Adjustable
Surface



Ingrade



Stainless-steel Underwater Luminaires

HueCraft Submersible series features an IP68-rated construction with a 316L stainless steel housing, corrosion-resistant fasteners, and an anti-aging waterproof silicone gasket. A clear safety glass lens and precision sealing protect internal components from water ingress, ensuring reliable operation in demanding underwater environments up to 16 ft deep.

LISTING



ELECTRICAL

Power Input	45W 120-277 VAc
Power Factor	> 0.9
Driver Location	Remote Location

PHYSICAL

Housing Material	316L Stainless Steel Housing, Anti-aging waterproof silicone gasket, Clear safety glass, Nickel plated brass cable gland
Finish	Stainless Steel
Dimensions	Adjustable Surface Mount: 5.91" x 3.46" x 6.44", ø5.91" Surface Mount: 6.69" x 6.69" x 5.9", ø6.69"
Weight	6.2 lbs / 2.8 kg
Adjustability	Tiltable 60°, Rotation 0 - 350°
Mounting	Adjustable Surface Mount, Inground

PHOTOMETRIC PERFORMANCE

Lumen Output	1,332 lm (25°)
Beam Angle	10°, 15°, 25°, 40°, 60°, 20°x40°
Colors	RGB + 3000K
Color Rendering	CRI 85+
Lumen Maintenance	Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 65,000 Hrs

CONTROL

Control	4 Channel DMX
Dimming	DMX 8 bit high resolution dims to 0.1%, supports ANSI E1.20 RDM protocol

ENVIRONMENTAL

Operating Temperature	32°F ~ 122°F / 0°C ~ 50°C
Ingress Protection	IP68
Impact Resistance	IK08
Listing	UL 379 (Remote Power Box) , UL 676 (Light Head), CE, FCC

WARRANTY

Warranty	5-year limited warranty
----------	-------------------------

CATALOG

PROJECT

TYPE

QUANTITY

PRODUCT CONFIGURATOR 

Try our **product configurator** on our website to easily specify your requirements and add items to a fixture list.

HS6			UNV		
MODEL	WATTAGE	CCT / CRI	VOLTAGE	DIMMING	OPTIC
HS6 HueCraft Submersible 6"	25 25W, Ø6"	C308 RGBW (3000K + RGB)	UNV 120 - 277 VAC	DMX DMX 8 bit high resolution dims to 0.1%, supports ANSI E1.20 RDM protocol	10 10° 15 15° 25 25° 40 40° 60 60° 2040 20° x 40°

ST	SUM	
FINISH	MOUNTING	CABLE
ST Stainless Steel	SUM Adjustable Surface Mount ING Ingrade	50 50ft 100 100ft 150 150ft

CATALOG - REMOTE POWER BOX

REMOTE POWER BOX


HSR4		NON
MODEL	OUTPUT PORT	OPTION
HSR4 HueCraft Submersible Remote Power Box (4ch)	1P 1 Port 2P 2 Ports 3P 3 Ports	NON No Terminator DMXT DMX Terminator Included

PERFORMANCE

	COLOR	LUMEN
10°	Red	110.8 lm
	Green	321.9 lm
	Blue	92.9 lm
	White	242.1 lm
	Full On	640.4 lm
15°	Red	108.7 lm
	Green	270.2 lm
	Blue	75.3 lm
	White	211.4lm
	Full On	628.4 lm
25°	Red	108.3 lm
	Green	269.2 lm
	Blue	75.1 lm
	White	210.6 lm
	Full On	626.1 lm
40°	Red	134.5 lm
	Green	334.3 lm
	Blue	93.2 lm
	White	261.5 lm
	Full On	777.4 lm
60°	Red	129.5 lm
	Green	291.6 lm
	Blue	81.3 lm
	White	228.1 lm
	Full On	678.1 lm
20x40°	Red	71.8 lm
	Green	178.5 lm
	Blue	49.8 lm
	White	139.6 lm
	Full On	415.1 lm

Note: Tolerance ±10%

PHOTOMETRICS



DMX CHART

The HueCraft Submersible 6 fixture is a four channel DMX unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

DMX ADDRESS


Fixture #	Channel	Red Control (ex. X)	Green Control (ex. X+1)	Blue Control (ex. X+2)	White (ex. X+3)
#1		1	2	3	4
#2		5	6	7	8
#3		9	10	11	12

COMPATIBLE DMX CABLING

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable must not be used to carry DMX. We recommend the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed. A DMX terminator is also required at the end of each DMX chain to ensure proper signal transmission and prevent data reflection.

CONNECTION

* This diagram is for illustrative purposes only. All installations must comply with applicable electrical codes and safety standards. Follow NEC requirements and consult a qualified professional for proper implementation.




Note:

- Maximum fixtures per remote power box: 4 fixtures
- Maximum fixtures per daisy chain: 32 fixtures


DIMENSIONS

ADJUSTABLE SURFACE MOUNT




DIMENSIONS

INGRADE



REMOTE POWER BOX



Note:

- The remote power box is IP65 rated and suitable for wet locations.